



BXR

BX 52R

3PH HYDRAULIC ROLLER FEED

With a PTO powered rotor and hydraulic feed hopper, branches, limbs and brush are control fed for continuous chipping at maximum capacity.

Wallenstein uses Pioneer style ball type hydraulic couplings for all tractor auxiliary connections. Substitutions are not available from Wallenstein and must be made at the customers expense.



STANDARD FEATURES

Adjustable Chute

Oversized Heavy Duty Rotor

Hardened Tool Reversible Chipper Blades

Slab style opening

Bearing Protection Plate



BX 52R

- 18-50 HP Range
 - 40-45 HP Required for Max. Capacity (BX52R)
 - 30-45 HP Required for Max. Capacity (BX52RI)
 - 5" x 10" Chipper Housing Opening
 - 24.75" Rotor with 4 Knives at 125 lbs.
 - Dimensions (LxWxH) 62" x 61" x 74"
 - 74" Discharge Hood Height, 270° rotation
 - 845 lbs. Total Weight
- BX 52RI: Includes Intellifeed

Quik Hitch and iMatch systems may require longer PTO shafts for optimum and safe performance, replacements are not available from Wallenstein and must be made at the customers expense. iMatch systems require adapter bushings not available from Wallenstein and must be purchased at the customers expense.